

**Asus® M2A-VM** **Mainboard**

Chipset	AMD® 690G, SB600 Southbridge
CPU Support	AMD® Skt AM2 Sempron®, Athlon® 64, Athlon® 64 X2 Processors
Memory Support	4 DDR2 SDRAM Slots, DDR2 533/667/800MHz Support, 4GB Max
Form Factor	uATX, 9.6" x 9.0"
Graphics	ATI® Radeon X1250 based Graphics, Up to 256MB Shared
Audio	Integrated Realtek® ALC883 High Def Audio Controller
Network	Integrated Realtek® 10/100/1000 LAN, PXE Boot
IDE Controller	1 40 Pin Connector, 2 Devices, Ultra DMA 33/66/100/133
SATA Controller	4 SATA Connectors, SATA 150/300, RAID 0 & 1
USB 2.0 & 1394	10 Total USB 2.0 Ports (4 Rear, 6 reserved for Front Panel Devices)
Standard I/O	1 Floppy Controller, PS2 Ports, 1 Parallel Port
Expansion Slots	1 PCI Express x16, 1 PCI Express x1, 2 PCI
BIOS	Award® Licensed, 8 Mbit, Hardware Monitoring
Regulatory / Certifications	FCC Class B, CE, & UL Listed, Microsoft WHQL, RoHs (Lead Free)

Product Images



PCB Picture



Back Panel I/O Ports

Note: DVI-D port cannot be converted to DVI-I or RGB

